



Physical characteristics

Construction	2x0,50mm ² + 2x0,60mm	
A1. Power conductor	Materials	Construction
Stranded copper wire	Cu	2 x 0,50 mm ²
A2. Signal conductor		
Solid soft annealed copper	Cu	2 x 0,60 mm
B1. Power conductor insulation		
Polyvinyl chloride	PVC	
Colors	Red - Black	
B2. Signal conductor insulation		
Polyethylene	PE	
Colors	Yellow - Blue	
C. Sheath		
Material and color	See table below	
Weight	See table below	
Minimum bending radius	5 times overall diameter	
Storage and operating temperature range	-40°C to +70°C	

Electrical characteristics

Power conductors resistance	38 Ω/km
Signal conductors resistance	62 Ω/km
Power conductors capacitance	81 pF/m
Signal conductors capacitance	42 pF/m
Power conductors inductance	620 μH/km
Signal conductors inductance	850 μH/km
Characteristic impedance	140 Ω
Sheath spark test	2 kVdc

Item	Weight [kg/km]	Outer diameter [mm]	Sheath color and material	Fire reaction classification
AJX 22 E NH	35,4	5,00	White LSZH with green stripe	Eca
AJX 22 F PE	29,0	5,00	Black PE	Fca

Condition of installation

Suitable for protected fixed installation in surface mounted or recessed ducts or similar enclosed systems. They can be installed in a single duct or channel or walkway without the interposition of separating walls.

Cable produced in compliance with the CEI UNEL 36762 standard, therefore suitable for laying in the same conduit with circuits of electrical systems with nominal voltage to earth up to 400 V, typically 230/400 V power systems.

Rated voltage: Cable for systems cat. 0, rated operating voltage not exceeding 50 V in alternating current and 120 V in direct current (not rippled).

Ref. CPR UE 305/11 Fire reaction classification

Cables for security systems with particular fire reaction characteristics compliant with the Construction Products Regulation (CPR). Reaction to fire classification: See reference product code in the box above to identify the relevant reaction to fire class.

Packaging

Type	Length	Description
SF100	100 m ± 2%	Shrink foil roll
WR500	500 m ± 2%	Wooden reel

European Directive Compliance: EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)

© 2024 BETA CAVI All Rights Reserved.

Although BETA CAVI makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. BETA CAVI provides the information and specifications with no representations or warranties, whether express, statutory or implied. BETA CAVI believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of BETA CAVI's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.